

## Alphacool Apex Thermal grease 1g

Alphacool article number: 13037



### Quick Info

The Alphacool Apex Thermal Grease is intended for all users who want to achieve the optimum performance with their system. With a high thermal conductivity, this electrically non-conductive thermal paste suitable for high contact pressures is clearly the favorite when performance and ease of application are required.

- Performance thermal paste with a high thermal conductivity
- Suitable for high contact pressures
- Easy to apply due to optimal viscosity

### Scope of delivery

1x Apex Thermal grease 1g

## Technical data

|                                   |  |
|-----------------------------------|--|
| Volatilization Rate (24H@200°C)%  | less than 0.5                                    |
| Density (g/cc)                    | 3.2 (Test method ASTM D792)                      |
| Viscosity (mPa.s)                 | 150-200*10 <sup>3</sup> (Test method ASTM D2196) |
| Continuous Using Temperature (°C) | -40°C to 120°C                                   |
| Breakdown Voltage (V/mil)         | 250 (Test method ASTM D149)                      |
| Thermal Impedance (°C in 2/W)     | 0.1 +/- 0.01 (Test method ASTM D5470)            |
| Max. working pressure (psi)       | 40   |
| Quantity                          | 1g   |
| Color                             | gray   |

## Download links

|                   |   |
|-------------------|---|
| Safety data sheet | <a href="#">13037_Alphacool_Apex_Thermal_grease_1g_SDS.pdf</a>  |
| Product pictures  | <a href="#">13037_Alphacool_Apex_Thermal_grease_1g_pics.zip</a> |

## Packaging dimensions per unit

|           |                  |
|-----------|------------------|
| L x W x H | 110 x 85 x 15 mm |
| Weight    | 4 g              |

## Other data

|              |               |
|--------------|---------------|
| Certificates | CE, FC, RoHS  |
| EAN          | 4250197130370 |
| Customs code | 84733080000   |

## Article text

The Alphacool Apex Thermal Grease is intended for all users who want to achieve the optimum performance with their system. With a high thermal conductivity, this electrically non-conductive thermal paste suitable for high contact pressures is clearly the favorite when performance and ease of application are required.

### Application

Apex Thermal Grease can be optimally applied due to its high viscosity. For perfect application of the thermal paste, a plastic spatula (not included) or a comparable tool should be used.

### Properties

Alphacool's Apex Thermal Grease has an extremely high thermal conductivity, making it one of the best performing thermal pastes on the market. Only liquid metal thermal pastes offer better thermal conductivity. The Apex Thermal Grease is delivered in a 1g applicator with screw cap. The Apex Thermal Grease is non-conductive and non-caustic. If a small amount of paste is spilled during application, damage to the hardware is highly unlikely.

### Range of uses

Alphacool's high-performance thermal paste can be used to cool electronic components of all kinds. In addition to CPUs and graphics cards, the components of Playstation and Xbox game consoles can also be cooled and thus significantly improved in their performance and durability.