

Alphacool Apex Thermal Pad Soft 16W/mk 100x100x1mm

Alphacool article number: 13492





Quick Info

Alphacool offers a wide range of thermal pads for effective heat dissipation of electric components. Among these, the Apex thermal pad is the most powerful option. It can reliably dissipate heat and is versatile due to its strong compressibility.

- High thermal conductivity
- Low thermal resistance
- Good electrical insulation
- High compressibility
- Natural tack

Scope of delivery

1x Apex Thermal Pad Soft 16W/mK 100x100x1mm

Technical data thermal pad

Dimensions (L x W x H)	100 x 100 x 1mm
Thermal Conductivity (ASTM D5470)	16.6 W/mK (±10%)
Hardness (ASTM D2240)	65 (Shore 00) (±5)
Working temperature	-50 to ~150°C
Volume Resistance (ASTM D257)	5×1012 Ohm-m
Dielectric Breakdown Voltage (ASTM D149)	5 KV/mm (±10%)
Density (ASTM D792)	3.6 g/cm³ (±10%)
Elongation (ASTM D412)	20%
Weight Loss (ASTM E595)	less than 1%
Flame Rating (UL 94)	V-0
Color	dark grey

Download links

Safety data sheet	13492_Alphacool_Apex_Thermal_Pad_Soft_16W-mk_100x100x1mm_SDS.pdf
Product pictures	13492_Alphacool_Apex_Thermal_Pad_Soft_16W-mk_100x100x1mm_pics.zip

Packaging dimensions per unit	
LxWxH	130 x 130 x 2 mm
Weight	51 g

Other data	
Certificates	CE, FC, RoHS
EAN	4250197134927
Customs code	84733080000

Article text

Alphacool offers a wide range of thermal pads for effective heat dissipation of electric components. Among these, the Apex thermal pad is the most powerful option. It can reliably dissipate heat and is versatile due to its strong compressibility.

Powerful!

Alphacool's Apex thermal pad is a silicone-based ultra-soft thermal pad with optimal compressibility. Due to its low hardness and natural stickiness, it perfectly adapts to surfaces, compensates for irregularities between components, and significantly improves heat transfer.

Increased lifespan!

Thanks to its unique material composition, the Apex thermal pad has a significantly reduced risk of silicone bleeding. It is capable of reliably cooling for a much longer period than conventional thermal pads without significant performance losses.

Versatile!

Due to its excellent electrical insulation, the thermal pad is also suitable for cooling electric components in a variety of devices, including electric vehicles, autopilot systems, mobile phones, servers, motherboards, power supplies, LCD TVs, notebooks, telecommunications devices, access points, memory modules, and much more.

Properties

Thermal Resistance vs. Pressure vs. Deflection

Pressure(psi)	R(°C-in²/W)	Deflection(%)					
10	0.209	19					
30	0.112	24					

Thermal Conductivity : 16.6 W/mK

Hardness: 65 (Shore 00)

0	0.8	1.2	1.4	1.6	1.7	1.8	2.2	3.2	3.6	4.0	4.5	5.0	1	5	20	0	5	1	0 1	15	20	25	3	0 4	0		80
														<u> </u>												~	

We assume no responsibility for any typing errors. Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com