Download Center

Alphacool NexXxoS UT60 Full Copper X-Flow 40mm Triple (3x40mm) Radiator

Alphacool article number: 14289

Quick Info

A fully copper server radiator that is compatible with 1U server racks. It provides space for 40 mm format fans that can be mounted on one or both sides. The radiator offers three connection options on each side and has holes for M3x5 screws on the top and bottom.

- Compatible with server racks in 1U format
- Solid copper radiator
- Many different connection options
- Patented countersunk screw plugs

Scope of delivery

1x mounting material

Technical data

L x W x H	164,5 x 60 x 40,5 mm
Quantity of cooling channels	9
Net weight	433 g
Max. working temperature	60 °C
Material cooling fins	Copper
Material cooling channels	Copper
Prechamber material	Copper
Material outer housing	Steel
Fins per Inch	12
Threads	6x G1/4“
Mounting options	4x M3 threads
Fan size	40 mm
Fan slots	3 one-sided / 6 double-sided
Fan threads	M3
Fan threads	0,8 Bar

Download links

Manual	14289_Alphacool_NexXxoS_UT60_Full_Copper_X-Flow_40mm_Triple_(3x40mm)_Radiator_Manual.pdf
Product pictures	14289_Alphacool_NexXxoS_UT60_Full_Copper_X-Flow_40mm_Triple_(3x40mm)_Radiator_pics.zip
EU-DoC / CE / RoHS	Alphacool_EuDoc_CE_RoHS_14289.pdf

Packaging dimensions per unit

L x W x H	310 x 70 x 55 mm
Weight	433 g

Other data

Certificates	CE, FC, RoHS
EAN	4250197142892
Customs code	84195080900

Article text

It's the best system because it's your system, strive for perfection! The new Alphacool NexXxoS UT60 X-Flow Server Radiators help you to get one step closer!

Increase the performance of your system with the new Alphacool NexXxoS UT60 X-Flow Server Radiators.

This Radiator can discharge up to 210 W at an ambient temperature of 30°C and fans with 12.000 rpm.

X-Flow – Find the easy route

For the best possible cooling of your system, Alphacool relies on the X-Flow for the new NexXxoS server radiators. The flow runs from one side of the radiator to the other and directly uses all fins. Your Alphacool NexXxoS UT60 X-Flow immediately achieves the best possible cooling with optimized water circulation.

Countersunk screw plugs - anything but ordinary

For the first time Alphacool has countersunk the screw plugs. This unique design allows you to stay flexible with the positioning of your Alphacool NexXxoS UT60 X-Flow Radiator. Mount your radiator the way you need it. Thanks to the multiple inlets and outlets, you have more options to create something unique and more importantly efficient.

Solid copper - the best performance at the highest level

The radiator of the new Alphacool NexXxoS series is also made of solid copper ensuring the radiators offer you the highest thermal conductivity for the best performance. Rely on the No. 1 in materials.

Different sizes - same quality

The new Alphacool NexXxoS UT60 X-Flow is available in different sizes and thicknesses. All radiators of this series are compatible with 2U server racks. Thanks to the special shape, installation is child's play, even with the larger radiators. Decide for yourself which size is perfect for your system and always choose the best quality.