

## Alphacool NexXxoS UT60 Full Copper X-Flow 40mm Penta (5x40mm) Radiator

Alphacool article number: 14291



### Quick Info

fully copper server radiator that is compatible with 1U server racks. It provides space for 40 mm format fans that can be mounted on one or both sides. The radiator offers three connection options on each side and has holes for M3x5 screws on the top and bottom.

- Compatible with server racks in 1U format
- Solid copper radiator
- Many different connection options
- Patented countersunk screw plugs

### Scope of delivery

1x mounting material

## Technical data

L x W x H	245,5 x 60 x 40,5 mm
Quantity of cooling channels	9
Net weight	577 g
Max. working temperature	60 °C
Material cooling fins	Copper
Material cooling channels	Copper
Prechamber material	Copper
Material outer housing	Steel
Fins per Inch	12
Threads	6x G1/4"
Mounting options	8x M3 thread
Fan size	40 mm
Fan slots	5 one-sided / 10 double-sided
Fan threads	M3
Pressure tested	0,8 bar

## Download links

Product pictures	<a href="#">14291_Alphacool_NexXxoS_UT60_Full_Copper_X-Flow_40mm_Penta_(5x40mm)_Radiator_pics.zip</a>
------------------	---

## Packaging dimensions per unit

L x W x H	310 x 70 x 55 mm
Weight	577 g

## Other data

Certificates	CE, FC, RoHS
EAN	4250197142915
Customs code	84195080900

It's the best system because it's your system, strive for perfection! The new Alphacool NexXoS UT60 X-Flow Server Radiators help you to get one step closer!

Increase the performance of your system with the new Alphacool NexXoS UT60 X-Flow Server Radiators.

This Radiator can discharge up to 350 W at an ambient temperature of 30°C and fans with 12.000 rpm.

### **X-Flow – Find the easy route**

For the best possible cooling of your system, Alphacool relies on the X-Flow for the new NexXoS server radiators. The flow runs from one side of the radiator to the other and directly uses all fins. Your Alphacool NexXoS UT60 X-Flow immediately achieves the best possible cooling with optimized water circulation.

### **Countersunk screw plugs - anything but ordinary**

For the first time Alphacool has countersunk the screw plugs. This unique design allows you to stay flexible with the positioning of your Alphacool NexXoS UT60 X-Flow Radiator. Mount your radiator the way you need it. Thanks to the multiple inlets and outlets, you have more options to create something unique and more importantly efficient.

### **Solid copper - the best performance at the highest level**

The radiator of the new Alphacool NexXoS series is also made of solid copper ensuring the radiators offer you the highest thermal conductivity for the best performance. Rely on the No. 1 in materials.

### **Different sizes - same quality**

The new Alphacool NexXoS UT60 X-Flow is available in different sizes and thicknesses. All radiators of this series are compatible with 2U server racks. Thanks to the special shape, installation is child's play, even with the larger radiators. Decide for yourself which size is perfect for your system and always choose the best quality.