

Alphacool NexXxoS UT60 Full Copper X-Flow 40mm Hexa (6x40mm) Radiator

Alphacool article number: 14292





Quick Info

It's the best system because it's your system, strive for perfection! The new Alphacool NexXxoS UT60 X-Flow Server Radiators help you to get one step closer! Increase the performance of your system with the new Alphacool NexXxoS UT60 X-Flow Server Radiators. This Radiator can discharge up to 420 W at an ambient temperature of 30°C and fans with 12.000 rpm.

- Compatible with server racks in 1U format
- Solid copper radiator
- Many different connection options
- · Patented countersunk screw plugs

Scope of delivery

1x Alphacool NexXxoS UT60 Full Copper X-Flow 40mm Hexa Radiator Mounting material

Technical data

Abmessungen (L x B x H)	286 x 40,5 x 60mm
Quantity of cooling channels	9
Thickness	49 - 69mm
Cooling channels	Copper
Color	black
Fan thread	M3
Connection	6x G1/4"
Slats	Copper
Housing	Steel
Pressure tested	0,8 bar
Manufacturer	Alphacool
Fins per inch	10
Fan size	40mm
Number of fans	6

Download links

 Manual
 14292_Alphacool_NexXxoS_UT60_Full_Copper_X-Flow_40mm_Hexa_(6x40mm)_Radiator_Manual.pdf

 Product pictures
 14292_Alphacool_NexXxoS_UT60_Full_Copper_X-Flow_40mm_Hexa_(6x40mm)_Radiator_pics.zip

Packaging dimensions per unit

LxWxH	420 x 75 x 50 mm
Weight	644 g

Other data

Certificates	CE, FC, RoHS
EAN	4250197142922
Customs code	84195080900

Article text

It's the best system because it's your system, strive for perfection! The new Alphacool NexXxoS UT60 X-Flow Server Radiators help you to get one step closer!

Increase the performance of your system with the new Alphacool NexXxoS UT60 X-Flow Server Radiators.

This Radiator can discharge up to 420 W at an ambient temperature of 30°C and fans with 12.000 rpm.

X-Flow - Find the easy route

For the best possible cooling of your system, Alphacool relies on the X-Flow for the new NexXxoS server radiators. The flow runs from one side of the radiator to the other and directly uses all fins. Your Alphacool NexXxoS UT60 X-Flow immediately achieves the best possible cooling with optimized water circulation.

Countersunk screw plugs - anything but ordinary

For the first time Alphacool has countersunk the screw plugs. This unique design allows you to stay flexible with the positioning of your Alphacool NexXxoS UT60 X-Flow Radiator. Mount your radiator the way you need it. Thanks to the multiple inlets and outlets, you have more options to create something unique and more importantly efficient.

Solid copper - the best performance at the highest level

The radiator of the new Alphacool NexXxoS series is also made of solid copper ensuring the radiators offer you the highest thermal conductivity for the best performance. Rely on the No. 1 in materials.

Different sizes - same quality

The new Alphacool NexXxoS UT60 X-Flow is available in different sizes and thicknesses. All radiators of this series are compatible with 2U server racks. Thanks to the special shape, installation is child's play, even with the larger radiators. Decide for yourself which size is perfect for your system and always choose the best quality.