

## Alphacool NexXoS UT60 Full Copper Dual-Flow 360mm Radiator

Alphacool article number: 14390



### Quick Info

Alphacool Dual-Flow radiators were developed specifically for use in servers. The ability to run two separate loops through one radiator is unique. There are also advantages to using them in a single loop as you can split the cooling surface and use it directly behind hotspots.

- Solid copper radiator
- Versatile connection options
- 2 separated waterways

### Scope of delivery

1x Alphacool NexXoS UT60 Full Copper Dual-Flow 360mm Radiator, Black	12x M3x45 screw
12x M3x8 screw	8x screw plug
12x M3x30 screw	1x Allen key

## Technical data

L x W x H	415 x 125 x 60 mm
Quantity of cooling channels	36
Material cooling fins	copper
Material cooling channels	copper
Prechamber material	copper
Material outer housing	steel
Fins per Inch	12
Threads	12x G1/4"
Thread size fan mounting	M3
Fan size	120 mm
Fan slots	3 one-sided / 6 double-sided
Pressure tested	0,8 bar
Max working temperature	60 °C
Weight	1537 g
Colour	Schwarz

## Download links

Product pictures	<a href="#">14390_Alphacool_NexXxoS_UT60_Full_Copper_Dual-Flow_360mm_Radiator_pics.zip</a>
------------------	--

## Packaging dimensions per unit

L x W x H	460 x 135 x 70 mm
Weight	1894 g

## Other data

Certificates	CE, FC, RoHS
EAN	4250197143905
Customs code	84195080900

Alphacool Dual-Flow radiators were developed specifically for use in servers. The ability to run two separate loops through one radiator is unique. There are also advantages to using them in a single loop as you can split the cooling surface and use it directly behind hotspots.

### **What does dual flow mean?**

The water flow in a classic radiator is in a U-shape. Water is introduced on one side, runs once through half of the radiator before turning around and running back through the other half. The outlet is on the same side as the inlet. In an X-Flow radiator, the water flows once from left to right completely through the radiator. The inlet and outlet are on opposite sides. With the Dual-Flow Radiator, the water flows from one side to the other just like the X-Flow. However, the Dual-Flow Radiator is divided in the middle. You could also say the Dual-Flow Radiator is nothing more than two small X-Flow Radiators in one.

### **What are the advantages?**

In most server racks, space is extremely limited and being able to do fancy loops is not usually an option. Due to this you can utilise the radiator to simplify the loop and reduce the amount of tubing needed. In some test scenarios, we have even seen an increase in performance from the loop due to this method too.

### **Many connection and mounting options**

The radiator offers 3 connection options at each input and output. In total, the radiator has 12x G1/4" connections. Thus, versatile mounting requirements can be met. The radiator comes with all screws for mounting inside a case or server rack and for mounting the fans. Additional screws are usually not needed. There is also a protective plate between the mounting holes and the cooling fins. This is to prevent overly long screws from damaging the cooling fins and cooling channels.

### **Choice of materials**

Alphacool is the only manufacturer in the world to use only copper in all water-carrying parts in the radiator. The pre-chambers and the cooling channels are made of copper. The connection threads are made of brass and the cooling fins are also made of copper. Only the side parts to protect the cooling fins are made of sheet steel.