Download Center

Alphacool Eiszapfen 13/10mm compression fitting 90° rotatable G1/4 4pcs Set Chrome

Alphacool article number: 17312

Quick Info

Alphacool's Eiszapfen connector series is the high-end execution of these tried-and-true fittings!

- For maximum flexibility, the threaded side can be rotated
- No compromise in form, finish and colouring

Scope of delivery

1x Alphacool Eiszapfen 13/10mm compression fitting 90° rotatable G1/4, 4pcs Set Chrome

We assume no responsibility for any typing errors. Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 7400 Supportmail: info@alphacool.com

Technical data

Material	brass
L x W x H	34,5 x 20 x 33mm
Threads	G1/4" OT | 13/10mm (ID 3/8" OD 1/2")
Thread length	5mm
Possible rotation	360°
Version	90° angled
Color	chrome

Download links

Product pictures	17312_Alphacool_Eiszapfen_13-10mm_compression_fitting_90_rotatable_G1-4_4pcs_Set_Chrome_pics.zip
EU-DoC / CE / RoHS	Alphacool_EuDoc_CE_RoHS_17312.pdf

Packaging dimensions per unit

L x W x H	95 x 90 x 35 mm
Weight	280 g

Other data

Certificates	CE, FC, RoHS
EAN	4250197176125
Customs code	74198090990

Article text

Alphacool's Eiszapfen connector series is the high-end execution of these tried-and-true fittings!

Everything you want in a compression fitting is here: highflow, form, processing and colour. A refusal to compromise in development and production has made the Eiszapfen series into what it is. Fittings are available in brilliant chrome or a deep, matte black, which will fit excellently into any system.

A special procedure binds the outer coating firmly to the surface, improving the longevity of the intense colour and preventing any chipping or peeling of the coating. Every connector now has the Alphacool logo, which along with their distinctive shape makes them unmistakable!

Model: 90° Socket 13/10mm

This connector has a G¼" thread on one side and is thereby compatible with 95% of components. The other side fits a 13/10mm hose. The middle of this connector is turned at a 90° angle in order to prevent complicated hose connections. The threaded side is rotatable for maximum flexibility.