

# Alphacool HF compression Fitting TPV - 12,7/7,6mm Straight - Black

Alphacool article number: 17637





## Quick Info

As part of the Alphacool Enterprise Solutions product line, the TPV fittings made of nylon were specifically designed for the use with TPV hoses. In combination with the appropriate TPV hose, this fitting ensures remarkable tensile strength.

- Nylon TPV fitting
- · Strong tensile strength
- · Metal barrier ring

## Scope of delivery

1x HF compression Fitting TPV - 12,7/7,6mm Straight - Black

#### Technical data

Dimensions (L x D)	28 x 20,5mm
Material	Nylon
Thread	G1/4"
Thread length	5mm
Tube size	12,7/7,6mm
Color	black

#### **Download links**

Product pictures 17637\_Alphacool\_HF\_compression\_Fitting\_TPV\_-\_12,7-7,6mm\_Straight\_-\_Black\_pics.zip

### Packaging dimensions per unit

LxWxH	105 x 85 x 20 mm
Weight	6 g

#### Other data

Certificates	CE, FC, RoHS
EAN	4250197176378
Customs code	74198090990
Guarantee	5 years

#### Article text

As part of the Alphacool Enterprise Solutions product line, the TPV fittings made of nylon were specifically designed for the use with TPV hoses. In combination with the appropriate TPV hose, this fitting ensures remarkable tensile strength.

#### **Enterprise Solutions fitting?**

Until now Alphacool used these TPV water cooling fittings for servers and workstations exclusively where durability and safety are of utmost importance. To meet these requirements, straight TPV fittings have a locking collar that secures the hose. This collar consists of a metal ring inside the fitting that latches onto the hose with hooks, preventing the TPV hose from being pulled out under normal conditions.

#### Nylon as material

The fitting is made of nylon to keep weight to a minimum. Nylon is not only highly resistant but also extremely durable. Additionally, nylon is compatible with copper and aluminum parts in the water loop, and it does not react with other materials in the system.