


## Alphacool ES Liquid GL50 (-40°C) 1000ml

Alphacool article number: 18599



### Quick Info

With ES Liquid GL50, Alphacool offers an industrial cooling liquid for high-performance cooling. Due to its composition, it protects against deposits, can flow easily through all types of rubber and plastic parts, and has a low maintenance requirement. Servers and workstations, in particular, benefit from these properties.

- High performance industrial cooling liquid
- Designed for -40°C to 90°C
- Ensures high durability
- Not miscible with other liquids!

### Scope of delivery

1x ES Liquid GL50 1000ml

## Technical data

Filling quantity	1000ml
Boiling point	90°C
Freezing point	-40°C
Color	blue
Type of liquid	Silicate liquid
Contains	Ethylenglycol, Diethylenglycol

## Note on use

<b>Warning</b>	Must not be mixed with other liquids!
----------------	---------------------------------------

## Download links

Safety data sheet	<a href="#">18599_Alphacool_ES_Liquid_GL50_(-40C)_1000ml_SDS.pdf</a>
Product pictures	<a href="#">18599_Alphacool_ES_Liquid_GL50_(-40C)_1000ml_pics.zip</a>

## Packaging dimensions per unit

L x W x H	85 x 85 x 284 mm
Weight	1210 g

## Other data

Certificates	CE, FC, RoHS
EAN	4250197185998
Customs code	3811900000

## Article text

With ES Liquid GL50, Alphacool offers an industrial cooling liquid for high-performance cooling. Due to its composition, it protects against deposits, can flow easily through all types of rubber and plastic parts, and has a low maintenance requirement. Servers and workstations, in particular, benefit from these properties.

### Maximum performance!

Alphacool's ES Liquid GL50 industrial cooling liquid is designed for temperatures between -40°C and 90°C. The thermal conductivity is reliable and at the highest level even at extreme temperatures. Foam formation is also not to be feared as the high-stress cooling liquid effectively prevents it. Despite its blue color, no deposits occur. On the contrary, ES Liquid GL50 protects the system sustainably and thus ensures low maintenance and high durability.

### Do not mix!

As it is a silicate liquid, it does not contain nitrates, phosphates, or amines. This means that no rubber or plastic is attacked and the product can be used neutrally in any system. However, it is important that ES Liquid GL50 **must not** be mixed with other liquids! If it is mixed, the warranty will be voided and its properties may be negatively affected.