

Alphacool NexXxoS XT45 Full Copper 240mm Radiator V.2 - White Special Edition

Alphacool article number: 18647



Quick Info

The NexXxoS V.2 radiator is the further development of the already established NexXxoS V.1 series and rightly takes its place among Alphacool's high-end full copper radiators. The fresh design in modern, noble white and the numerous technical details make the NexXxoS V.2 radiator the perfect partner for your own water cooling system.

- patented screw plugs
- new, modern design
- solid copper radiator

Scope of delivery

1x Alphacool NexXxoS XT45 Full Copper 240mm Radiator V.2, White Special Edition	3x screw plug
8x M3x8 screw	1x Allen key
8x M3x30 screw	1x screw plug tool
2x M3x35 screw	

Technical data

L x W x H	272,1 x 124 x 45 mm (+/- 3% tolerance in the range of the prechamber)
Material cooling fins, channels & prechamber	copper
Material outer housing	steel
Fins per Inch	12
Threads	5x G1/4"
Thread size fan mounting	M3
Fan size	120 mm
Fan slots	2 one-sided / 4 double-sided
Max working temperature	60 °C
Weight	868 g
Colour	Weiss
Pressure tested	0,8 bar

Download links

Manual	18647_Alphacool_NexXoS_XT45_Full_Copper_240mm_Radiator_V.2_-_White_Special_Edition_Manual.pdf
Product pictures	18647_Alphacool_NexXoS_XT45_Full_Copper_240mm_Radiator_V.2_-_White_Special_Edition_pics.zip

Packaging dimensions per unit

L x W x H	345 x 135 x 55 mm
Weight	1012 g

Other data

Certificates	CE, FC, RoHS
EAN	4250197186476
Customs code	84195080900
Guarantee	10 years

The NexXoS V.2 radiator is the further development of the already established NexXoS V.1 series and rightly takes its place among Alphacool's high-end full copper radiators. The fresh design in modern, noble white and the numerous technical details make the NexXoS V.2 radiator the perfect partner for your own water cooling system.

Uncompromising in the choice of materials

Alphacool is the only manufacturer worldwide to use exclusively copper for all water-bearing parts in the radiator. The pre-chambers, cooling fins and cooling channels are all made of pure copper. The only exceptions are the threaded inserts (made of brass) and the outer casing of the radiator (made of sheet steel).

Sufficient cooling capacity

To maximise the performance of the radiator, Alphacool reaches deep into its bag of tricks and uses pure copper for the cooling fins, cooling channels and pre-chambers due to the high thermal conductivity of 400 W/mK (in comparison: aluminium 236 W/mK). The special fin density of the radiator with a fin spacing of 15 FPI give optimal airflow and performance. All cooling fins are additionally serrated. These act as tiny wings that direct the airflow in the desired direction and ensure controlled air turbulence. This increases the cooling capacity and minimises possible flow noise.

Patented screw plugs

All NexXoS V.2 radiators use Alphacool's patented stop fittings. Anyone who has mounted a radiator on the front or in the roof of a case is familiar with the fact that protruding stop fittings can stop the radiator from sitting flush. With the patented stop fittings, Alphacool offers an excellent solution. The stop fittings are completely recessed in the radiator and sit flush with its surface. This means that nothing stands in the way of a clean installation. Of course, the radiators also look much more elegant with the flat stop fittings.

Plenty of connection options

All versions of the NexXoS V.2 radiators have two options for IN and OUT on each side. On the opposite end is a fill or vent port, which can also be used to drain the water circuit.

Safety first

The NexXoS V.2 radiator has a special protective plate that prevents fan or mounting screws from being screwed in too deeply. These plates are beneath the screw holes that are used to mount the fans to the radiator, or for mounting the radiator to the case. This protects the cooling fins and water channels underneath from damage.